



Q[®] SERIES

Serial Technology with 31 Available Color Settings: Single, Dual, Tri, Quad, & Quint.

Feniex Industries, Inc.
1.800.615.8350

Q-DUAL SURFACE MOUNT

Perimeter



PART #	QDSMS-8101
DIMENSIONS	5.25" x 0.88" x 2.25"
VOLTAGE	10-18VDC
CURRENT DRAW	2 Amps @ 13V
INPUTS	27 Inputs
FLASH PATTERNS	Over 20
OPTICS	60° Wide Spread
LED COLORS	
LED COUNT	54 LEDs
CABLE LENGTH	1ft

CERTIFICATIONS:



DESCRIPTION:

Introducing the Feniex Q-Dual Surface Mount (Serial), the first 5-color, smart perimeter light, with two modules on a Double Bezel for twice the brightness. Engineered with precision and innovation, this cutting-edge surface mount light offers a spectrum of colors including blue, red, amber, white, and green, empowering you to command attention and enhance safety in any situation. The Feniex Q[®] Series lightheads are built with state-of-the-art serial technology that connects using 2 serial wires to the Q[®] Link device.

- Blue, Red, Amber, White, and Green colors in each module
- Syncs with up to 48 lightheads using one Q Link
- Computer programmable with Q Link Software
- 27 programmable inputs with the Q Link (sold separately)
- Available functions include Flood, Cruise, and Stop Tail Turn and more



Surface Mount Wire Harness



Military-grade aluminum



Anti-yellowing & anti-cracking clear-coated polycarbonate lens