

## G-FLAT-DUAL 3-MODE PART DIMENSIONS DIMENSIONS Perimeter Voltage CURRENT DR MODES FLASH PATTE OPTICS LED COLORS LED COLORS

3-MODE PART #	QFD-8101
DIMENSIONS	5.25" x 0.56" x 2.25"
VOLTAGE	10-18VDC
CURRENT DRAW	2 Amps @ 13V
MODES	3 Modes
FLASH PATTERNS	14 Patterns
OPTICS	60° Wide Spread
LED COLORS	
LED COUNT	54 LEDs
CABLE LENGTH	1ft

## CERTIFICATIONS:



## DESCRIPTION:

Introducing the Feniex Q-Flat-Dual Surface Mount (3-Mode), the first 5-color, low-profile, smart perimeter light. Engineered for a stream-lined, sleek exterior, this cutting-edge surface mount light offers a spectrum of colors including Blue, Red, Amber, White, and Green, empowering you to command attention and enhance safety in any situation. The Feniex Q<sup>®</sup> Series is built with state-of-the-art smart modules compatible with any 12V switch or controller, syncs with all Feniex smart modules using 3-mode technology, and boasts bright 60-degree optics for exceptional visibility.

- Blue, Red, Amber, White, and Green colors in each module
- Hardwire installation syncs with all Quad, Lux, and Q Series products
- Available functions include Flood, Cruise, and Stop Tail Turn and more
- Color-lock mode available during installation





Anti-yellowing & anticracking clear-coated polycarbonate lens