

OSERIES

Serial Technology with 31 Available Color Settings: Single, Dual, Tri, Quad, & Quint.

▲ Q-FLATSURFACE MOUNT



| PART# | QFMS-8101 |
|----------------|-------------------|
| DIMENSIONS | 5.5" x 0.56" x 1" |
| VOLTAGE | 10-18VDC |
| CURRENT DRAW | 1 Amp @ 13V |
| INPUTS | 27 Inputs |
| FLASH PATTERNS | Over 20 |
| OPTICS | 60° Wide Spread |
| LED COLORS | |
| LED COUNT | 27 LEDs |
| CABLE LENGTH | 1ft |

MOUNTING:













VEHICLE SPECIFIC:



CERTIFICATIONS:













DESCRIPTION:

Introducing the Feniex Q-Flat-Surface Mount (Serial), the first 5-color, low-profile, serial perimeter light. Engineered for a stream-lined, sleek exterior, this cutting-edge surface mount light offers a spectrum of colors including Blue, Red, Amber, White, and Green, empowering you to command attention and enhance safety in any situation. The Feniex Q® Series lightheads are built with state-of-the-art serial technology that connects using 2 serial wires to the Q® Link device.

- Blue, Red, Amber, White, and Green colors in each module
- Syncs with up to 48 lightheads using one Q Link
- Computer programmable with Q Link Software
- 27 programmable inputs with the Q Link (sold separately)
- \blacksquare Available functions include Flood, Cruise, and Stop Tail Turn and more



